

CLAIMS

Please amend the claims as follows:

1. (Currently amended) A method comprising:

grouping single fields of a multiple-field source into a search target having a plurality of multiple-field keys (MFKs) whose, each MFK having single fields that correspond to [[the]] single fields in one of a plurality of multiple-field vectors (MFVs) of entries in a data structure;

generating a set of queries based, at least in part, on the MFKs, wherein each query includes one or more of the MFKs and wherein each query has a different MFK as a lead MFK;

using a query to determine whether the non-wildcard values in the MFVs of an entry match the non-wildcard values in corresponding MFKs of the search target; and

using, if no entry has non-wildcard values in the MFVs that match the corresponding non-wildcard values in the MFKs, the queries to determine whether the entry has non-wildcard values in a MFV that match the non-wildcard values in a corresponding lead MFK, plus remaining MFVs that match corresponding remaining MFKs based on matching the non-wildcard values and wildcard values.

2. (Original) The method of claim 1, wherein the entries of the data structure are stored such that the MFVs that have non-wildcard values are located at the end of the entry.

3. (Original) The method of claim 1, further comprising arranging the entries of the data structure so that the MFVs that have non-wildcard values are placed at the end of the entry.

4. (Original) The method of claim 1, wherein the non-wildcard values comprise a fixed value and/or a range of fixed values.

5. (Original) The method of claim 1, further comprising:
locating the entry having non-wildcard values in the MFV that match the non-wildcard values in the corresponding lead MFK, plus remaining MFVs that match corresponding remaining MFKs based on matching the non-wildcard values and wildcard values; and
performing an operation associated with the located entry.

6. (Original) The method of claim 1, wherein the multiple-field source comprises a data packet having single fields in its header.

7. (Original) The method of claim 6, wherein the operation comprises one of the following: dropping the data packet, mirroring, metering, traffic shaping, rate limiting, accounting, statistics gathering, providing quality of service (QoS), redirecting to a central processing unit (CPU) for further processing, or sampling a subset of the packets to a CPU.

8. (Original) The method of claim 1, wherein fewer than all MFVs in the entries include one single field.

9. (Original) The method of claim 1, wherein the MFVs in the entries include two or more single fields.

10. (Currently amended) An apparatus comprising:

a data structure having a plurality of entries, wherein each entry has a group of multiple-field vectors (MFVs) that each include a number of single fields having all wildcard values or all non-wildcard values; and

a search unit to group single fields of a multiple-field source into a search target having a plurality of multiple-field keys (MFKs) ~~whose each MFK having~~ single fields that correspond to the single fields in ~~multiple-field vectors (MFVs) in a corresponding MFV of the~~ entries in ~~[[a]] the~~ data structure, generate a set of queries based, at least in part, on the MFKs, wherein each query includes one or more of the MFKs and has a different MFK as a lead MFK, use a query to determine whether the non-wildcard values in the MFVs of an entry match the non-wildcard values in corresponding MFKs of the search target; and use, if no entry has non-wildcard values in the MFVs that match the corresponding non-wildcard values in the MFKs, the queries to determine whether the entry has non-wildcard values in a MFV that match the non-wildcard values in a corresponding lead MFK, plus remaining MFVs that match corresponding remaining MFKs based on matching the non-wildcard values and wildcard values..

11. (Original) The apparatus of claim 10, wherein the entries of the data structure are stored such that the MFVs that have non-wildcard values are located at the end of the entry.

12. (Original) The apparatus of claim 10, wherein the search unit arranges the entries of the data structure so that the MFVs that have non-wildcard values are placed at the end of the entry.

13. (Original) The apparatus of claim 10, wherein the non-wildcard values comprise a fixed value and/or a range of fixed values.

14. (Original) The apparatus of claim 10, wherein the search unit locates the entry having non-wildcard values in the MFV that match the non-wildcard values in the corresponding lead MFK, plus remaining MFVs that match corresponding remaining MFKs based on matching the non-wildcard values and wildcard values; and performs an operation associated with the located entry;

15. (Original) The apparatus of claim 10, wherein the multiple-field source comprises a data packet having single fields in its header.

16. (Original) The apparatus of claim 15, wherein the operation comprises one of the following: dropping the data packet, mirroring, metering, traffic shaping, rate limiting, accounting, statistics gathering, providing quality of service (QoS), redirecting to a central processing unit (CPU) for further processing, or sampling a subset of the packets to a CPU.

17. (Original) The apparatus of claim 10, wherein fewer than all MFVs in the entries include one single field.

18. (Original) The apparatus of claim 10, wherein the MFVs in the entries include two or more single fields.

19. (Currently amended) An article of manufacture comprising:
a machine-accessible medium including thereon sequences of instructions that, when executed, cause an electronic system to:

group single fields of a multiple-field source into a search target having multiple-field keys (MFKs) whose, each MFK having single fields that correspond to [[the]] single fields in one of a plurality of multiple-field vectors (MFVs) of entries in a data structure;

generate a set of queries based, at least in part, on the MFKs, wherein each query includes one or more of the plurality of MFKs and wherein each query has a different MFK as a lead MFK;

use a query to determine whether the non-wildcard values in the MFVs of an entry match the non-wildcard values in corresponding MFKs of the search target; and

use, if no entry has non-wildcard values in the MFVs that match the corresponding non-wildcard values in the MFKs, the queries to determine whether the entry has non-wildcard values in a MFV that match the non-wildcard values in a corresponding lead MFK, plus remaining MFVs that match corresponding remaining MFKs based on matching the non-wildcard values and wildcard values.

20. (Original) The article of manufacture of claim 19, wherein the entries of the data structure are stored such that the MFVs that have non-wildcard values are located at the end of the entry.

21. (Original) The article of manufacture of claim 19, wherein the machine-accessible medium further comprises sequences of instructions that, when executed, cause the electronic system to arrange the entries of the data structure so that the MFVs that have non-wildcard values are placed at the end of the entry.

22. (Currently amended) The ~~method~~ article of manufacture of claim 19, wherein the non-wildcard values comprise a fixed value and/or a range of fixed values.

23. (Original) The article of manufacture of claim 19, wherein the machine-accessible medium further comprises sequences of instructions that, when executed, cause the electronic system to:

locate the entry having non-wildcard values in the MFV that match the non-wildcard values in the corresponding lead MFK, plus remaining MFVs that match corresponding remaining MFKs based on matching the non-wildcard values and wildcard values; and

perform an operation associated with the located entry.

24. (Original) The article of manufacture of claim 19, wherein the multiple-field source comprises a data packet having single fields in its header.

25. (Original) The article of manufacture of claim 24, wherein the operation comprises one of the following: dropping the data packet, mirroring, metering, traffic shaping, rate limiting, accounting, statistics gathering, providing quality of service (QoS), redirecting to a central processing unit (CPU) for further processing, or sampling a subset of the packets to a CPU.

26. (Original) The article of manufacture of claim 19, wherein fewer than all MFVs in the entries include one single field.

27. (Original) The article of manufacture of claim 24, wherein the MFVs in the entries include two or more single fields.

28. (Currently amended) A system, comprising:

a processor;

a network interface coupled with the processor; and

an article of manufacture comprising a machine-accessible medium including thereon sequences of instructions that, when executed, cause an electronic system to:

group single fields of a multiple-field source into a search target having a plurality of multiple-field keys (MFKs) whose, each MFK having single fields that correspond to the single fields in one of a plurality of multiple-field vectors (MFVs) of entries in a data structure;

generate a set of queries based, at least in part, on the MFKs, wherein each query includes one or more of the plurality of MFKs and has a different MFK as a lead MFK;

use a query to determine whether the non-wildcard values in the MFVs of an entry match the non-wildcard values in corresponding MFKs of the search target; and

use, if no entry has non-wildcard values in the MFVs that match the corresponding non-wildcard values in the MFKs, the queries to determine whether the entry has non-wildcard values in a MFV that match the non-wildcard values in a corresponding lead MFK, plus remaining MFVs that match corresponding remaining MFKs based on matching the non-wildcard values and wildcard values.

29. (Currently amended) The ~~method~~ system of claim 28, wherein the non-wildcard values comprise a fixed value and/or a range of fixed values.

30. (Currently amended) The ~~article of manufacture~~ system of claim 28, wherein the multiple-field source comprises a data packet having single fields in its header.